

Malleable Iron Fittings Price List



Since this metal is an alloy of iron carbon , Malleable Iron Pipe Fittings Manufacturers treat the alloy with heat. During its initial cast, iron does not have any graphite and all the carbon content is in the form of cementite. As understood by Malleable Iron Fittings Manufacturers In Thailand, typically it has alloyants in the following quantity - 2 % to 3 % carbon, 1% to 2 % silicone, 0 % to 1 % manganese. Apart from these elements, the Malleable Iron Fittings manufacturers add trace amounts of elements such as sulfur and phosphorus.

MALLEABLE IRON THREADED FITTINGS PRICE LIST

GENERAL NOTES

MINIMUM INVOICE:	\$50.00 net
PRICES:	All prices are each. Taxes extra as applicable
F.O.B. :	Our plant, stocking warehouse. Any single order having a total order value of \$1000 or more for shipment to a single destination, will have full freight allowed at the lowest published rate for the most economical way. Shipments to remote locations may, at our option, be subject to less than full freight allowance.
PAYMENT TERMS:	Net 30 days.
OTHER TERMS:	The "General Terms and Conditions" apply to all orders.

Malleable Iron Fittings

Malleable iron fittings, steel welded nipples, merchant steel couplings, forged steel fittings. merchant steel fittings, forged steel ansi flanges, steel butt-weld fittings, bronze fittings. Bronze & Lead-Free Bronze Fittings. brass nipples, stainless steel cast fittings, stainless steel nipples, stainless steel forged fittings.

www.skylandmetal.in

Check Malleable Iron Fittings List In India.

Buy Large Or Small Quantity At Factory Price Of Anvil Malleable Iron Fittings, We Malleable Iron Fittings Suppliers In UAE & UK.

View Black Malleable Iron Fittings Dimensions & Pressure Rating Malleable Iron Fittings, Global supplier of malleable iron threaded pipe fittings.

As recommended by Malleable Iron Fittings suppliers in UAE, engineers prefer using this alloy for parts that require to be coined, pierced or cold-formed. Malleable Iron Fittings Class 150 works well for those parts that need to have the most machinability. Which means that parts like Malleable Iron Pipe Fittings are easy to produce using a machine by manufactures.



Malleable Iron Fittings Manufacturers In India

[Special offer on black malleable iron fittings with best price, Shop huge inventory of anvil malleable iron fittings and malleable iron pipe fittings, Discounted galvanized malleable iron fittings Price In India.](#)

Malleable iron pipe fittings can come in two types of finishes i.e. - black and galvanized finishes. While there are three forms of malleable cast iron, they include - blackheart, whiteheart and pearlitic malleable cast iron. The surface region of the whiteheart Class 300 Malleable Iron Fittings has ferrite. While the intermediate zone of the Malleable Cast Iron Pipe Fittings has temper carbon, ferrite and pearlite. Tempering done by the Malleable Cast Iron Fittings Manufacturers ensures hardening of metal. Blackheart malleable cast iron is mostly consists of ferrite. And pearlitic malleable cast iron is composed of both pearlite as well as other austenite products. Pearlite in turn is made up of or is formed by alternating layers of both ferrite and cementite.

[Check All malleable iron socket weld fittings price list by Top Fittings manufacturer, We will better any competitor's price on our stocked items for welding malleable iron pipe fittings and threaded malleable iron fittings, We are supplying anvil malleable iron fittings & malleable iron pipe fittings to more than 60 locations worldwide, Latest Price With Latest Offer on galvanised malleable iron pipe fittings.](#)

Malleable Iron Fittings for pipe is the conduit system of choice for solar heating systems. Most solar heating systems that are meant for interior heat and hot water supplies use a dense fluid, which then traps solar energy. This dense fluid becomes too hot. Hence, a PVC piping system is not able to tolerate the heat and may either deform or get damaged. On the other hand Malleable Iron Fitting Pressure Ratings with different classes is ideal to transport this dense, yet hot fluid. Therefore all the Malleable Iron Fitting Dimensions of a solar heat system can be used to create a piping system. Further most suppliers of Malleable Iron Fittings UK also recommend using them for cold water plumbing, because these fittings retain their shape even in the coldest conditions. Malleable Iron Fittings manufacturers in India promote the use of galvanized pipe fittings across various sectors. Especially prior to installation in a plumbing system, many of these fittings are galvanized. This is because in galvanized fittings, the outer layer has been zinc coated, which in turn prevents corrosion like rust.



Check malleable iron pipe fittings dimensions

Class 150 Malleable Iron Threaded Fittings											ASTM A197		ANSI B16.3	
	NPS ▲ DN	1/8" 3	1/4" 6	3/8" 10	1/2" 15	3/4" 20	1" 25	1-1/4" 32	1-1/2" 40	2" 50	2-1/2" 65	3" 80	4" 100	6" 150
90° Elbows	\$ BLACK	12.40	12.40	12.40	10.08	14.59	22.39	33.59	44.80	67.22	130.42	198.72	360.29	1428.55
	\$ GALV	14.99	14.99	14.99	12.28	17.72	27.31	40.93	54.58	81.88	157.55	240.11	435.20	
	WEIGHT	0.07	0.11	0.15	0.22	0.35	0.55	0.93	1.1	1.8	2.9	3.9	8.2	8.6
	CRTN QTY	50	35	45	50	30	20	20	10	8	15	10	5	2
45° Elbows	\$ BLACK	13.62	13.62	13.62	10.08	15.15	22.39	36.48	44.80	67.22	155.27	236.06	403.77	2291.00
	\$ GALV	16.53	16.53	16.53	12.28	18.39	27.31	44.34	54.58	81.88	187.61	285.21	487.65	
	WEIGHT	0.07	0.11	0.15	0.22	0.31	0.51	0.75	0.97	1.6	2.4	3.3	6.2	6.4
	CRTN QTY	50	35	50	50	40	20	20	15	9	15	10	6	2
Tees	\$ BLACK	15.59	15.59	15.59	12.89	18.45	29.08	43.71	56.01	84.04	198.72	260.87	472.08	1676.98
	\$ GALV	18.78	18.78	18.78	15.64	22.53	35.48	53.20	68.26	102.32	240.11	315.14	570.22	
	WEIGHT	0.09	0.11	0.2	0.24	0.42	0.66	1.1	1.3	2	3.6	5	9.3	11.2
	CRTN QTY	75	50	45	40	35	20	14	11	6	10	6	4	1
Coupling	\$ BLACK	9.32	9.32	9.32	7.85	10.62	17.95	25.23	30.82	47.64	93.18	136.64	223.55	683.23
	\$ GALV	11.29	11.29	11.29	9.59	12.94	21.84	30.69	37.54	58.04	112.62	165.04	270.15	
	WEIGHT	0.07	0.07	0.11	0.18	0.26	0.44	0.62	0.9	1.2	1.9	2.6	4.6	6
	CRTN QTY	60	40	50	60	50	25	32	18	12	16	12	7	1
Caps	\$ BLACK	8.69	8.69	8.69	7.85	9.55	13.43	19.66	25.74	35.81	80.83	111.83	186.31	712.76
	\$ GALV	10.62	10.62	10.62	9.59	11.58	16.36	23.93	31.44	43.60	97.60	135.07	225.13	
	WEIGHT	0.04	0.04	0.09	0.11	0.18	0.31	0.53	0.57	0.88	1.5	1.9	3.5	4
	CRTN QTY	100	200	50	50	40	35	25	25	18	30	20	14	2
Square Head Plugs	\$ BLACK	10.58	10.58	10.58	8.42	10.89	11.22	16.82	19.66	28.07	62.17	87.00	155.27	509.11
	\$ GALV	13.62	13.62	13.62	11.96	15.87	17.95	20.52	23.93	34.19	74.98	105.00	187.61	
	WEIGHT	0.02	0.02	0.04	0.09	0.11	0.15	0.26	0.35	0.55	0.97	1.4	2.5	3.4
	CRTN QTY	100	100	100	40	25	40	25	24	15	40	30	8	5
Unions Brass To Iron	\$ BLACK	55.90	55.90	55.90	50.37	64.42	75.69	100.84	134.37	201.60	372.69	621.15	1232.07	
	\$ GALV	67.54	67.54	67.54	61.40	78.60	92.10	122.88	161.16	245.51	450.16	749.23	1498.40	
	WEIGHT	0.1	0.2	0.31	0.42	0.56	0.93	1.3	1.7	2.6	4.6	5.7	10.1	
	CRTN QTY	30	30	35	30	25	20	18	12	8	10	5	3	
Crosses	\$ BLACK	31.09	31.09	31.09	31.09	43.43	58.96	87.00	118.02	161.50	351.31	498.95	926.57	
	\$ GALV	37.54	37.54	37.54	37.54	52.54	71.26	105.00	142.58	195.09				
	WEIGHT	0.15	0.17	0.31	0.3	0.49	0.79	1.3	1.5	2.4	4.6	6.1	6.7	
	CRTN QTY	80	80	60	45	30	16	9	8	5	6	4	2	
Floor Flanges	\$ BLACK			34.74	34.74	48.17	56.24	80.20	93.68	113.66				
	\$ GALV			42.04	42.04	58.22	67.86	96.95	113.06	137.39				
	WEIGHT			0.5	0.57	0.68	0.82	1.2	1.5	2.1				
	CRTN QTY			25	25	20	20	15	12	8				
Locknuts	\$ BLACK	10.18	10.18	10.18	10.18	8.11	10.01	13.07	16.73	26.06				
	\$ GALV	12.85	12.85	12.85	9.78	9.78	12.05	15.80	20.23	31.49				
	WEIGHT	0.1	0.1	0.1	0.57	0.68	0.82	1.2	1.5	2.1				
	CRTN QTY	250	125	100	100	60	40	30	45	25				

= Diameter Nominal, metre equivalent of NPS

* = Carton Quantities for Individual reducing fittings are available on request.

Note: Weights are given in pounds per piece. To convert to kilograms, multiply pounds by 0.45



Class 150 Malleable Iron Threaded Fittings											ASTM A197		ANSI B16.3	
	NPS ▲ DN	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
		3	6	10	15	20	25	32	40	50	65	80	100	150
90° Street Elbows	\$ BLACK	13.62	13.62	13.62	12.40	18.03	26.77	46.63	57.15	80.83	180.17	279.49	465.83	
	\$ GALV	16.53	16.53	16.53	14.99	21.75	32.32	56.30	69.07	97.60	217.59	337.68	562.79	
	WEIGHT	0.07	0.09	0.13	0.22	0.33	0.55	0.88	1.1	1.8	2.9	3.9	8.4	
	CRTN QTY	50	35	40	60	30	30	20	13	7	13	8	4	
45° Street Elbows	\$ BLACK	18.63	18.63	18.63	18.63	28.57	37.86	62.17	74.48	124.22	248.40	372.69	558.95	
	\$ GALV	27.98	27.98	27.98	22.55	34.51	45.79	74.98	90.02	150.10				
	WEIGHT	0.06	0.09	0.13	0.17	0.29	0.46	0.79	0.93	1.5	2.3	3.3	6.2	
	CRTN QTY	50	35	45	100	60	30	20	15	9	15	10	6	

Class 150 Malleable Iron Reducing Threaded Fittings					ASTM A197		ANSI B16.3	
Reducing 90° Elbows				Reducing 90° Elbows				
Size	Wt	Blk	Galv	Size	Wt	Blk	Galv	
1/4" -- 3/8" -- 1/2"				1-1/2 x 3/4	1.4	54.67	66.00	
1/4 x 1/8	0.11	14.84	21.75	1-1/2 x 1/2	1.4	54.67	66.00	
3/8 x 1/4	0.19	14.84	21.75	2"				
3/8 x 1/8	0.19	14.84	21.75	2 x 1-1/2	3.6	80.83	97.60	
1/2 x 3/8	0.29	13.62	16.53	2 x 1-1/4	2.3	80.83	97.60	
1/2 x 1/4	0.29	13.62	16.53	2 x 1	2.3	80.83	97.60	
1/2 x 1/8	0.29	13.62	16.53	2 x 3/4	2.3	80.83	97.60	
3/4"				2 x 1/2	2.3	80.83	97.60	
3/4 x 1/2	0.46	18.03	21.75	2 -1/2"				
3/4 x 3/8	0.46	18.03	21.75	2-1/2 x 2	3.6	167.71	245.95	
3/4 x 1/4	0.46	18.03	21.75	2-1/2 x 1-1/2	3.6	167.71	245.95	
3/4 x 1/8	0.46	18.03	21.75	2-1/2 x 1-1/4	3.6	167.71	245.95	
1"				2-1/2 x 1	3.6	167.71	245.95	
1 x 3/4	0.71	27.38	33.06	2-1/2 x 3/4	3.6	167.71	245.95	
1 x 1/2	0.71	27.38	33.06	2-1/2 x 1/2	3.6	167.71	245.95	
1 x 3/8	0.71	27.38	33.06	3"				
1 x 1/4	0.71	27.38	33.06	3 x 2-1/2	4.4	280.05	559.12	
1-1/4"				3 x 2	4.4	280.05	559.12	
1-1/4 x 1	0.95	44.11	53.23	3 x 1-1/2	4.4	280.05	559.12	
1-1/4 x 3/4	0.95	44.11	53.23	4"				
1-1/4 x 1/2	0.95	44.11	53.23	4 x 3	6.2	560.01		
1-1/2"				4 x 2-1/2	6.2	560.01		
1-1/2 x 1-1/4	1.4	54.67	66.00	4 x 2	6.2	560.01		
1-1/2 x 1	1.4	54.67	66.00					

= Diameter Nominal, metre equivalent of NPS

* = Carton Quantities for Individual reducing fittings are available on request.

Note: Weights are given in pounds per piece. To convert to kilograms, multiply pounds by 0.45



Class 150 Malleable Iron Reducing Threaded Fittings								ASTM A197	ANSI B16.3			
Reducing Couplings				Reducing Couplings				Reducing Couplings				
Size	WT	Blk	Galv	Size	WT	Blk	Galv	Size	WT	Blk	Galv	
1/4" -- 3/8" -- 1/2"				1-1/4 x 3/4	0.55	29.19	35.23	2-1/2 x 1-1/4	1.6	99.34	120.04	
1/4 x 1/8	0.08	10.57	12.78	1-1/4 x 1/2	0.55	29.19	35.23	2-1/2 x 1	1.6	99.34	120.04	
3/8 x 1/4	0.11	10.57	12.78	1-1/4 x 3/8	0.55	29.19	35.23	2-1/2 x 3/4	1.6	99.34	120.04	
3/8 x 1/8	0.11	10.57	12.78	1-1/2"				2-1/2 x 1/2	1.6	99.34	120.04	
1/2 x 3/8	0.18	10.57	12.78	1-1/2 x 1-1/4	0.7	34.82	42.10	3"				
1/2 x 1/4	0.18	10.57	12.78	1-1/2 x 1	0.7	34.82	42.10	3 x 2-1/2	2.4	155.27	187.61	
1/2 x 1/8	0.18	10.57	12.78	1-1/2 x 3/4	0.7	34.82	42.10	3 x 2	2.4	155.27	187.61	
3/4"				1-1/2 x 1/2	0.7	34.82	42.10	3 x 1-1/2	2.4	155.27	187.61	
3/4 x 1/2	0.22	13.43	16.36	1-1/2 x 3/8	0.7	34.82	42.10	3 x 1-1/4	2.4	155.27	187.61	
3/4 x 3/8	0.22	14.84	18.01	2"				3 x 1	2.4	155.27	187.61	
3/4 x 1/4	0.22	14.84	18.01	2 x 1-1/2	1.0	52.81	63.77	4"				
3/4 x 1/8	0.22	14.84	18.01	2 x 1-1/4	1.0	52.81	63.77	4 x 3	4.2	285.70	345.11	
1"				2 x 1	1.0	52.81	63.77	4 x 2-1/2	4.2	285.70	345.11	
1 x 3/4	0.35	17.95	21.84	2 x 3/4	1.0	52.81	63.77	4 x 2	4.2	285.70	345.11	
1 x 1/2	0.35	19.86	23.95	2 x 1/2	1.0	52.81	63.77	4 x 1-1/2	4.2	285.70	345.11	
1 x 3/8	0.35	19.86	23.95	2 x 3/8	1.0	52.81	63.77	4 x 1-1/4	4.2	285.70	345.11	
1 x 1/4	0.35	19.86	23.95	2-1/2"				6"				
1-1/4"				2-1/2 x 2	1.6	99.34	120.04	6 x 4	4.9	967.30		
1-1/4 x 1	0.55	29.19	35.23	2-1/2 x 1-1/2	1.6	99.34	120.04					

Class 150 Malleable Iron Reducing Threaded Fittings								ASTM A197	ANSI B16.3			
Reducing Bushings				Reducing Bushings				Reducing Bushings				
Size	WT	Blk	Galv	Size	WT	Blk	Galv	Size	WT	Blk	Galv	
1/4" -- 3/8" -- 1/2"				1-1/4 x 3/8	0.29	24.86	30.04	2-1/2 x 1	0.7	68.29	82.54	
1/4 x 1/8	0.05	15.92	24.88	1-1/4 x 1/4	0.29	24.86	30.04	2-1/2 x 3/4	0.7	68.29	82.54	
3/8 x 1/4	0.06	15.92	24.88	1-1/2"				2-1/2 x 1/2	0.7	68.29	82.54	
3/8 x 1/8	0.06	15.92	24.88	1-1/2 x 1-1/4	0.31	29.19	35.23	3"				
1/2 x 3/8	0.07	9.32	11.29	1-1/2 x 1	0.31	29.19	35.23	3 x 2-1/2	1.5	99.34	120.04	
1/2 x 1/4	0.07	9.32	11.29	1-1/2 x 3/4	0.31	29.19	35.23	3 x 2	1.5	99.34	120.04	
1/2 x 1/8	0.07	9.32	11.29	1-1/2 x 1/2	0.31	29.19	35.23	3 x 1-1/2	1.5	99.34	120.04	
3/4"				1-1/2 x 3/8	0.31	29.19	35.23	3 x 1-1/4	1.5	99.34	120.04	
3/4 x 1/2	0.11	10.57	12.78	1-1/2 x 1/4	0.31	29.19	35.23	3 x 1	1.5	99.34	120.04	
3/4 x 3/8	0.11	10.57	12.78	1-1/2 x 1/8	0.31	29.19	35.23	3 x 3/4	1.5	114.94	120.04	
3/4 x 1/4	0.11	10.57	12.78	2"				4"				
3/4 x 1/8	0.11	10.57	12.78	2 x 1-1/2	0.7	36.48	44.34	4 x 3	3.1	186.31	225.13	
1"				2 x 1-1/4	0.7	36.48	44.34	4 x 2-1/2	3.1	186.31	225.13	
1 x 3/4	0.20	14.04	17.04	2 x 1	0.7	40.35	48.70	4 x 2	3.1	186.31	225.13	
1 x 1/2	0.20	14.04	17.04	2 x 3/4	0.7	40.35	48.70	4 x 1-1/2	3.1	186.31	225.13	
1 x 3/8	0.20	15.59	18.83	2 x 1/2	0.7	40.35	48.70	4 x 1-1/4	3.1	186.31	225.13	
1 x 1/4	0.20	15.59	18.83	2 x 3/8	0.7	40.35	48.70	4 x 1	3.1	186.31	225.13	
1 x 1/8	0.20	17.84	21.36	2 x 1/4	0.7	40.35	48.70	6"				
1-1/4"				2-1/2"				6 x 4	10.3	509.11		
1-1/4 x 1	0.29	22.39	27.31	2-1/2 x 2	0.7	68.29	82.54	6 x 3	10.3	509.11		
1-1/4 x 3/4	0.29	24.86	30.04	2-1/2 x 1-1/2	0.7	68.29	82.54					
1-1/4 x 1/2	0.29	24.86	30.04	2-1/2 x 1-1/4	0.7	68.29	82.54					

= Diameter Nominal, metre equivalent of NPS

* = Carton Quantities for Individual reducing fittings are available on request.

Note: Weights are given in pounds per piece. To convert to kilograms, multiply pounds by 0.45



Class 150 Malleable Iron Reducing Threaded Fittings								ASTM A197	ANSI B16.3			
Reducing Tees				Reducing Tees				Reducing Tees				
Size	WT	Blk	Galv	Size	WT	Blk	Galv	Size	WT	Blk	Galv	
1/4 -- 3/8	--	1/2"		1-1/4 x 3/4 x 1-1/4	1.1	58.96	71.26	2 x 1-1/2 x 1-1/2	2.1	105.56	127.57	
1/4 x 1/4 x 1/8	0.12	24.94	33.56	1-1/4 x 3/4 x 1	1.1	58.96	71.26	2 x 1-1/2 x 1-1/4	2.1	105.56	127.57	
3/8 x 3/8 x 1/4	0.20	24.94	33.56	1-1/4 x 3/4 x 3/4	1.1	58.96	71.26	2 x 1-1/2 x 1	2.1	105.56	127.57	
1/2 x 1/2 x 1	0.28	39.13	N/A	1-1/4 x 3/4 x 1/2	1.1	58.96	71.26	2 x 1-1/2 x 3/4	2.1	105.56	127.57	
1/2 x 1/2 x 3/4	0.28	25.50	30.76	1-1/4 x 1/2 x 1-1/4	1.1	58.96	71.26	2 x 1-1/2 x 1/2	2.1	105.56	127.57	
1/2 x 1/2 x 3/8	0.28	21.14	25.50	1-1/4 x 1/2 x 1	1.1	58.96	71.26	2 x 1-1/4 x 2	2.1	105.56	127.57	
1/2 x 1/2 x 1/4	0.28	21.14	25.50	1-1/4 x 1/2 x 3/4	1.1	58.96	71.26	2 x 1-1/4 x 1-1/2	2.1	105.56	127.57	
3/4"				1-1/4 x 1/2 x 1/2	1.1	58.96	71.26	2 x 1-1/4 x 1-1/4	2.1	105.56	127.57	
3/4 x 3/4 x 1	0.42	39.13	47.29	1-1/2"				2 x 1-1/4 x 1	2.1	105.56	127.57	
3/4 x 3/4 x 1/2	0.42	23.00	33.56	1-1/2 x 1-1/2 x 2	1.3	105.56	127.57	2 x 1 x 2	2.1	105.56	127.57	
3/4 x 3/4 x 3/8	0.42	26.52	33.56	1-1/2 x 1-1/2 x 1-1/4	1.3	74.48	90.02	2 x 1 x 1-1/2	2.1	105.56	127.57	
3/4 x 3/4 x 1/4	0.42	25.50	33.56	1-1/2 x 1-1/2 x 1	1.3	74.48	90.02	2 x 1 x 1	2.1	105.56	127.57	
3/4 x 1/2 x 1	0.42	39.13	47.29	1-1/2 x 1-1/2 x 3/4	1.3	67.22	90.02	2 x 3/4 x 2	2.1	105.56	127.57	
3/4 x 1/2 x 3/4	0.42	25.50	30.76	1-1/2 x 1-1/2 x 1/2	1.3	74.48	90.02	2 x 1/2 x 2	2.1	105.56	127.57	
3/4 x 1/2 x 1/2	0.42	25.50	30.76	1-1/2 x 1-1/4 x 2	1.3	105.56	127.57	2-1/2"				
1"				1-1/2 x 1-1/4 x 1-1/2	1.3	74.48	90.02	2-1/2 x 2-1/2 x 2	3.3	217.43	262.65	
1 x 1 x 2	0.62	105.56	127.57	1-1/2 x 1-1/4 x 1-1/4	1.3	74.48	90.02	2-1/2 x 2-1/2 x 1-1/2	3.3	217.43	262.65	
1 x 1 x 1-1/2	0.62	74.48	N/A	1-1/2 x 1-1/4 x 1	1.3	74.48	90.02	2-1/2 x 2-1/2 x 1-1/4	3.3	217.43	262.65	
1 x 1 x 1-1/4	0.62	58.96	N/A	1-1/2 x 1-1/4 x 3/4	1.3	74.48	90.02	2-1/2 x 2-1/2 x 1	3.3	217.43	262.65	
1 x 1 x 3/4	0.62	35.26	42.98	1-1/2 x 1-1/4 x 1/2	1.3	74.48	90.02	2-1/2 x 2-1/2 x 3/4	3.3	217.43	262.65	
1 x 1 x 1/2	0.62	35.26	42.98	1-1/2 x 1 x 1-1/2	1.3	74.48	90.02	2-1/2 x 2-1/2 x 1/2	3.3	217.43	262.65	
1 x 1 x 3/8	0.62	39.13	47.29	1-1/2 x 1 x 1-1/4	1.3	74.48	90.02	2-1/2 x 2 x 2	3.3	217.43	262.65	
1 x 1 x 1/4	0.62	39.13	47.29	1-1/2 x 1 x 1	1.3	74.48	90.02	2-1/2 x 1-1/2 x 2	3.3	217.43	262.65	
1 x 3/4 x 1	0.62	39.13	47.29	1-1/2 x 1 x 3/4	1.3	74.48	90.02	3"				
1 x 3/4 x 3/4	0.62	39.13	47.29	1-1/2 x 1 x 1/2	1.3	74.48	90.02	3 x 3 x 2-1/2	4.9	310.54	429.90	
1 x 3/4 x 1/2	0.62	39.13	47.29	1-1/2 x 3/4 x 1-1/2	1.3	74.48	90.02	3 x 3 x 2	4.9	310.54	429.90	
1 x 1/2 x 1	0.62	39.13	47.29	1-1/2 x 3/4 x 1-1/4	1.3	74.48	90.02	3 x 3 x 1-1/2	4.9	310.54	429.90	
1 x 1/2 x 3/4	0.62	39.13	47.29	1-1/2 x 3/4 x 1	1.3	74.48	90.02	3 x 3 x 1-1/4	4.9	310.54	429.90	
1 x 1/2 x 1/2	0.62	39.13	47.29	1-1/2 x 3/4 x 3/4	1.3	74.48	90.02	3 x 3 x 1	4.9	310.54	429.90	
1-1/4"				1-1/2 x 3/4 x 1/2	1.3	74.48	90.02	3 x 3 x 3/4	4.9	310.54	429.90	
1-1/4 x 1-1/4 x 2	1.1	105.56	127.57	1-1/2 x 1/2 x 1-1/2	1.3	74.48	90.02	4"				
1-1/4 x 1-1/4 x 1-1/2	1.1	74.48	90.02	1-1/2 x 1/2 x 1	1.3	74.48	90.02	4 x 4 x 3	9.9	590.04	712.87	
1-1/4 x 1-1/4 x 1	1.1	58.96	71.26	1-1/2 x 1/2 x 3/4	1.3	74.48	90.02	4 x 4 x 2-1/2	9.9	590.04	712.87	
1-1/4 x 1-1/4 x 3/4	1.1	58.96	71.26	2"				4 x 4 x 2	9.9	590.04	712.87	
1-1/4 x 1-1/4 x 1/2	1.1	58.96	71.26	2 x 2 x 2-1/2	2.1	217.43	262.65	4 x 4 x 1-1/2	9.9	590.04	712.87	
1-1/4 x 1-1/4 x 3/8	1.1	58.96	71.26	2 x 2 x 1-1/2	2.1	105.56	127.57	4 x 4 x 1-1/4	9.9	590.04	712.87	
1-1/4 x 1-1/4 x 1/4	1.1	58.96	71.26	2 x 2 x 1-1/4	2.1	105.56	127.57	4 x 4 x 1	9.9	590.04	712.87	
1-1/4 x 1 x 1-1/4	1.1	58.96	71.26	2 x 2 x 1	2.1	95.18	115.96					
1-1/4 x 1 x 1	1.1	58.96	71.26	2 x 2 x 3/4	2.1	95.18	115.96					
1-1/4 x 1 x 3/4	1.1	53.24	71.26	2 x 2 x 1/2	2.1	105.56	126.38					
1-1/4 x 1 x 1/2	1.1	58.96	71.26	2 x 1-1/2 x 2	2.1	105.56	127.57					

= Diameter Nominal, metre equivalent of NPS

* = Carton Quantities for Individual reducing fittings are available on request.

Note: Weights are given in pounds per piece. To convert to kilograms, multiply pounds by 0.45



Class 300 Malleable Iron Threaded Fittings									ASTM A197		ANSI B16.3	
	NPS ▲ DN	1/4" 6	3/8" 10	1/2" 15	3/4" 20	1" 25	1-1/4" 32	1-1/2" 40	2" 50	2-1/2" 65	3" 80	4" 100
90° Eblows	\$ BLACK	18.26	18.26	15.73	18.55	29.66	42.56	60.80	91.20	167.18	286.94	
	\$ GALV			21.98	25.21	38.90	57.84	77.69	307.54		307.54	
	WEIGHT	0.2	0.29	0.5	0.77	1.2	1.8	2.4	3.8	6.3	9.5	
	CRTN QTY	25	25	50	30	25	15	10	6	3	2	
45° Elbows	\$ BLACK	23.12	23.12	25.73	27.47	33.45	52.14	68.61	106.38	204.96	298.11	
	\$ GALV			31.89	35.41	46.41	64.55	81.86	136.25			
	WEIGHT	0.19	0.28	0.44	0.7	1.1	1.7	2.2	3.4	5.6	8.3	
	CRTN QTY	20	50	25	25	10	12	5	15	4	2	
Tees	\$ BLACK	22.03	22.03	23.36	27.83	39.53	63.84	83.58	130.69	260.88	341.91	
	\$ GALV			32.63	38.90	53.23	83.95	111.97	173.91		459.76	
	WEIGHT	0.29	0.42	0.67	1.1	1.7	2.6	3.4	5.3	8.4	12.8	
	CRTN QTY	25	25	25	16	20	14	10	7	15	10	
Coupling	\$ BLACK	13.98	13.98	15.46	16.73	27.57	46.01	59.42	85.11	168.07	245.94	
	\$ GALV			19.22	22.65	25.12	57.10	73.79	117.49		301.39	
	WEIGHT	0.17	0.26	0.44	0.72	1.1	1.7	2.1	3.5	5.4	7.4	
	CRTN QTY	100	50	30	20	15	12	8	16	10	8	
Caps	\$ BLACK			17.89	17.89	23.87	26.10	38.03	52.94			
	\$ GALV			17.57	19.22	25.12	32.38	47.19	65.68			
	WEIGHT			0.26	0.39	0.62	0.98	1.3	1.9			
	CRTN QTY			20	40	25	15	10	6			
Unions Brass To Iron	\$ BLACK	37.99	50.15	40.68	47.10	58.72	95.40	99.98	142.86	393.35	544.23	
	\$ GALV	68.61	69.80	66.44	71.75	95.36	132.97	160.11	192.19	324.87	596.66	
	WEIGHT	0.3	0.4	0.64	0.97	1.5	2.2	2.6	4.2	7.3	10.5	
	CRTN QTY	50	50	50	35	16	12	10	6	5	7	
90° Street Elbows	\$ BLACK			23.87	33.92	39.89	54.78	71.56	105.67			
	\$ GALV											
	WEIGHT			0.39	0.61	0.98	1.49	2.04	3.24			
	CRTN QTY			30	15	10	8	8	5			
Reducing Coupling	\$ BLACK			22.19	22.74	27.57	42.56	52.42	85.11	144.38	253.36	
	\$ GALV				28.19							
	WEIGHT			0.25	0.55	0.83	1.3	1.8	2.8	4.5	5.9	
	CRTN QTY			10	60	30	15	20	14	8	6	
Reducing Tees	\$ BLACK				41.94	51.26	70.81	91.31	137.15			
	\$ GALV											
	WEIGHT				0.85	1.28	2	2.5	4			
	CRTN QTY				15	10	12	8	6			

= Diameter Nominal, metre equivalent of NPS

* = Carton Quantities for Individual reducing fittings are available on request.

Note: Weights are given in pounds per piece. To convert to kilograms, multiply pounds by 0.45